

## SAFETY DATA SHEET

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** CHLORINATED RUBBER SWIMMING POOL PAINT

**PRODUCT CODE:** Aquamarine, Ocean Blue, Black, Red, White

**PRODUCT USE:** For Professional use only

MANUFACTURED FOR

Wechsler Pool Supply Co.

216 East Broadway

Monticello, NY 12701 Phone: 866-444-POOL (7665)

**24 HR. EMERGENCY TELEPHONE NUMBER**

CHEMTREC: 1-800-424-9300 or 1-703-527-3887

### 2. HAZARDS IDENTIFICATION

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

**CLASSIFICATION:**

FLAMMABLE LIQUIDS - Category 2

ACUTE TOXICITY: Inhalation - Category 4

ASPIRATION HAZARD: Category 1

CARCINOGENICITY: Category 2

SKIN IRRITATION: Category 2

EYE IRRITATION: Category 2

SPECIFIC TARGET ORGAN TOXICITY: SINGLE EXPOSURE - Category 3

SPECIFIC TARGET ORGAN TOXICITY: REPEATED EXPOSURE - Category 2

#### GHS label elements

#### PICTOGRAMS



**SIGNAL WORD:** Danger

**HAZARD STATEMENTS:** Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin and serious eye irritation. Harmful if inhaled. May cause respiratory irritation, drowsiness or dizziness. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure.

#### **PRECAUTIONARY STATEMENTS:**

**PREVENTION:** Read all warning statements on all labels for this and any other products to be mixed with it prior to use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, and other tools or equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fumes, gas, mist, vapors or spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Use personal protective equipment as required, (see Section 8). Wear protective gloves, protective clothing, eye and face protection. Wear an appropriate, properly fitted fresh air supplied respirator (NIOSH-approved TC19 or equivalent) during and after application, and until all organic solvent vapors and spray mists are exhausted, or any time airborne contaminant levels exceed exposure limits indicated in Section 8. If medical advice is needed, have product container or label at hand.

**RESPONSE:** IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water or shower. If skin irritation or rash occurs: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If continued difficulty breathing is experienced, seek immediate medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing then seek immediate medical attention. If exposed or concerned: Get medical attention. Call a POISON CENTER, doctor or physician if you feel unwell.

Avoid release to environment. If spilled, contain material with inert absorbent, in compliance with local, regional and national regulations.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction, do not use water, see Section 5.

**STORAGE:** Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

**DISPOSAL:** Dispose of unused amounts and empty container with an approved waste disposal facility, in compliance with local, regional and national regulations.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range % by Weight
TERTIARY BUTYL ACETATE	540-88-5	30 - 45 %
TITANIUM DIOXIDE	13463-67-7	10 - 25 %
ALKYD	Mixture	5 - 15 %
CHLORINATED RUBBER	9006-03-5	5 - 15 %
AROMATIC NAPHTHA	64742-95-6	5 - 15 %
MAGNESIUM SILICATE	14807-96-6	5 - 15 %
1,2,4-TRIMETHYLBENZENE	95-63-6	1 - 5 %
MINERAL SPIRITS	64742-88-7	1 - 5 %

### 4. FIRST AID MEASURES

**EYES:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, check for and remove contact lenses. Seek immediate medical attention.

**SKIN:** Remove contaminated clothing. Immediately flush exposed area with large amounts of water. If skin irritation occurs, seek immediate medical attention. Wash clothing separately and clean shoes before reuse.

**INGESTION:** Seek immediate medical attention, contact physician or poison control center. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

**INHALATION:** Seek immediate medical attention. Remove from exposure to fresh air. If not breathing or if breathing is irregular, provide artificial respiration or oxygen by trained personnel; rescuers should put on appropriate protective gear. To prevent aspiration, keep head below knees. This coating contains materials classified as nuisance particles, (listed as "Resp. Dust" in Section 8), which may be present at hazardous levels during sanding or abrading of the dried film, do not breath dust.

**NOTES TO PHYSICIAN:** This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Symptoms of poisoning may appear several hours later. Toxicological information listed in Section 11.

### 5. FIRE FIGHTING MEASURES

**SUITABLE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Alcohol-resistant Foam. Do not use water, material will float and may ignite on surface of water.

**FIRE FIGHTING PROCEDURES:** Fight as volatile liquid fire. Wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Eliminate all sources of ignition. Evacuate unnecessary personnel. Use water spray to cool containers with caution, avoid spreading burning liquid. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

**UNUSUAL FIRE AND EXPLOSION HAZARD:** Highly Flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Vapors/dust may cause flash fire or explosion. This material may be ignited by heat, sparks, flame or static electricity. Closed containers may explode when exposed to extreme heat. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

### 6. ACCIDENTAL RELEASE MEASURES

**ENVIRONMENTAL PRECAUTIONS:** Avoid runoff and contact with soil, drains, sewers and waterways. Contact appropriate authority in compliance with local/regional/national regulations.

**PERSONAL PRECAUTIONS:** Eliminate all ignition sources. No smoking, do not use flares. Contact emergency personnel. Evacuate the spill area and keep unnecessary, unprotected personnel away. Do not breathe vapors, use suitable personal protective equipment. Do not touch or walk through spilled material. Prevent additional discharge of material if able to do so safely. Ventilate spill area.

**METHOD OF CLEANING UP:** For small spills, absorb with inert material, (dry sand or soil may be used in the absence of other non-combustible suitable materials) and use a non-sparking or explosion-proof means to transfer material to an appropriate container for disposal. For large spills, dike spilled material, or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal using non-sparking tools.

Dispose of spilled material and contaminated absorbent material in compliance with local and national regulations, use a licensed waste disposal contractor, see Section 13.

### 7. HANDLING AND STORAGE

**PRECAUTIONS FOR SAFE HANDLING:** Use only in a well ventilated area, with appropriate personal protective equipment, (see section 8). Do not eat, drink or smoke when handling this material. Wash hands and face before eating, drinking or smoking. Do not breathe vapor, fumes or mist. Do not get in eyes, or on skin, or clothing.

Always open containers slowly to allow any excess pressure to vent. Containers should be grounded when pouring. Take precautionary measures against static discharge. When transferring, follow proper grounding procedures. Use spark-proof tools and explosion proof equipment. Empty containers retain product residue and can be hazardous. Do not reuse container.

**CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES:** Store in accordance with local regulations. Store locked up. Keep container closed when not in use. Isolate from heat, flame, sparks, pilot lights, smoking materials and other sources of ignition. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated, explosion proof area. Protect from direct sunlight. KEEP OUT OF REACH OF CHILDREN AND PETS AT ALL TIMES.

## 8. EXPOSURE CONTROLS\PERSONAL PROTECTION

Components	CAS	Exposure Limits
TERTIARY BUTYL ACETATE	540-88-5	ACGIH TWA 200 PPM OSHA PEL TWA 200 PPM
TITANIUM DIOXIDE	13463-67-7	ACGIH TLV 10mg/m3 OSHA PEL TWA 15mg/m3 , total dust
ALKYD	Mixture	Data not available
CHLORINATED RUBBER	9006-03-5	Data not available
AROMATIC NAPHTHA	64742-95-6	Data not available
MAGNESIUM SILICATE	14807-96-6	ACGIH TLV 2mg/m3 Resp. Dust
1,2,4-TRIMETHYLBENZENE	95-63-6	ACGIH TWA 25 PPM
MINERAL SPIRITS	64742-88-7	Data not available

**ENGINEERING CONTROLS:** Provide explosion proof exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

**SKIN:** Wear impervious gloves to prevent contact with the skin. Where contact is likely, wear chemical resistant gloves, a chemical suit, long sleeves, rubber boots, and chemical safety goggles plus a face shield.

**RESPIRATORY:** Personal protective equipment should be selected for specific applications. Users should consider factors which affect exposure potential such as handling practices, chemical concentrations and ventilation. When airborne contaminate levels exceed exposure limits wear an appropriate, properly fitted fresh air-supplied respirator, (NIOSH-approved TC-19C or equivalent), during and after application, until all organic vapors and spray mists are exhausted. Follow respirator manufacturer's directions for respirator use.

**WORK HYGIENIC PRACTICES:** Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid  
 COLOR: Liquid in various colors  
 ODOR: Typical  
 ODOR THRESHOLD: Not available  
 pH: Not available  
 MELTING POINT: Not available  
 BOILING POINT: 208° F  
 FLASH POINT AND METHOD: 40°F  
 FLAMMABLE LIMITS: 1 - 8  
 EVAPORATION RATE: Not available  
 FLAMMABILITY (Solid/Gas): Not applicable  
 VAPOR PRESSURE: Not available  
 VAPOR DENSITY: Heavier than air  
 % SOLUBILITY IN WATER: Slight  
 OCTANOL/WATER PARTITION COEFFICIENT: Not available  
 AUTO-IGNITION TEMPERATURE: Not available  
 DECOMPOSITION TEMPERATURE: Not available

	AQUAMARINE	OCEANBLUE	WHITE	RED	BLACK
DENSITY:	9.9	10	10.4	8.9	8.8
SPECIFIC GRAVITY:	1.2	1.2	1.3	1.1	1.1
VOLATILE WEIGHT:	46.023	45.226	43.28	47.364	49.236
VOLATILE VOLUME:	62.816	62.581	62.437	58.491	60.129
EXEMPT V.O.C. WT %:	37.76	36.65	32.62	38.96	43.29
EXEMPT V.O.C. VOL %:	51.59	50.77	47.08	48.16	52.84
REGULATORY V.O.C. g/l:	201.79	208.78	251.5	173.4	133.27
ACTUAL V.O.C. g/l:	97.69	102.79	133.29	89.9	62.85

**10. STABILITY AND REACTIVITY**

**HAZARDOUS POLYMERIZATION:** Under normal conditions of storage and use, hazardous polymerization will not occur.

**CONDITIONS TO AVOID:** Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke, extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, tools, appliances and any other possible sources of ignition prior to spray application, during use and until all vapors are exhausted from the area.

**CHEMICAL STABILITY:** The product is stable. Avoid heat, open flame, sparks, static electricity, freezing.

**INCOMPATIBLE MATERIALS:** Alkaline materials, strong acids and oxidizing materials.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Under normal conditions of use and storage, hazardous reactions will not occur.

**11. TOXICOLOGICAL INFORMATION**

Individual component data, (where available):

**TERTIARY BUTYL ACETATE(540-88-5)**

Acute Dermal Toxicity	LD50: >2,000 mg/kg	Repeated exposure may cause skin dryness or cracking.
Acute Inhalation Toxicity	LC50: 12.52 mg/l 4hrs Category 4	Harmful if inhaled.
Acute Oral Toxicity	LD50: 4,500 mg/kg	
Aspiration Toxicity	Can cause pulmonary edema if aspirated into lungs.	
Target Organ, Single Exposure	Central Nervous System, Respiratory Category 3 May cause respiratory irritation. May cause drowsiness or dizziness.	
Eye Irritation	May cause moderate eye irritation.	
Symptoms of Overexposure	The onset of respiratory symptoms may be delayed for several hours after exposure. High doses may cause CNS depression.	

**TITANIUM DIOXIDE(13463-67-7)**

Acute Dermal Toxicity	LD50: >5,000 mg/kg (rabbit)	
Acute Inhalation Toxicity	LC50: >6.8 mg/l 4hrs (rat)	
Acute Oral Toxicity	LD50: >5,000 mg/kg (rat)	
Carcinogenicity Classification	IARC Group 2B Possibly carcinogenic to humans.	

**ALKYD Component: Mineral Spirits (64742-88-7)**

Acute Dermal Toxicity	LD50: 3,000 mg/kg (rabbit)	
Acute Inhalation Toxicity	LC50: >5.28 mg/L (rat)	
Acute Oral Toxicity	LD50: >5,000 mg/kg (rat)	
Aspiration Toxicity	Category 2 May be fatal if swallowed and enters airways.	
Target Organ, Repeat Exposure	May cause damage to organs through prolonged or repeated exposure.	
Eye Irritation	Category 2 Causes serious eye irritation.	
Skin Irritation	Category 2 Causes skin irritation.	
Symptoms of Overexposure	Headache, dizziness, tiredness, nausea and vomiting.	

**AROMATIC NAPHTHA (64742-95-6)**

Acute Dermal Toxicity	LD50: >3,160 mg/kg (rat) (OECD Test Guideline 402)	
Acute Inhalation Toxicity	LC50: >6193 mg/m <sup>3</sup> (rat 4hrs) (OECD Test Guideline 403)	May be irritating to the respiratory tract.
Acute Oral Toxicity	LD50: 3,492 mg/kg (rat) (OECD Test Guideline 401)	
Aspiration Toxicity	Category 1 May be fatal if swallowed and enters airways.	
Eye Irritation	Category 2 Causes serious eye irritation.	
Skin irritation	Category 2 Causes skin irritation.	
Carcinogenicity Classification	IARC Group 2B	Possibly carcinogenic to humans.

**12. ECOLOGICAL INFORMATION**

Individual component data, (where available):

**TERTIARY BUTYL ACETATE(540-88-5)**

Acute aquatic toxicity	Classified - Harmful to aquatic life.	
Toxicity to fish	Acute toxicity to fish is very low.	
Toxicity to daphnia and other aquatic invertebrates	Acute toxicity to freshwater and marine invertebrates is very low.	
Toxicity to algae	Can inhibit growth of aquatic algae	EC50: 16 ml/l 72hrs
Toxicity to bacteria	High concentrations may be harmful to sewage treatment plant microbes 1.5 mg/l	
Persistence and degradability	Biodegradability	Inherently biodegradable
Bioaccumulative potential	Bioaccumulation - Not expected to bioaccumulate	

**AROMATIC NAPHTHA (64742-95-6)**

Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LL50: 10 mg/l 96hrs
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EL50: 4.5 mg/l 48hrs
Toxicity to algae	Pseudokirchneriella subcapitata (green algae)	EL50: 3.1 mg/l 72hrs
Persistence and degradability	Biodegradability	Readily
Bioaccumulation Potential	Partition coefficient: n-octanol/water	log Pow: 3.42 (25° C)

**13. DISPOSAL CONSIDERATIONS**

**RECOMMENDATIONS:** The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection, waste disposal legislation and any regional local authority requirements. Empty containers should be disposed of through an approved waste management facility.

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, ensure conformity to all applicable hazardous waste regulations, consult your local or regional authorities.

## 14. TRANSPORT INFORMATION

**UN NUMBER:** UN1263

**UN PROPER SHIPPING NAME:** PAINT

**TRANSPORT HAZARD CLASS:** 3

**PACKING GROUP:** II

**SPECIAL PRECAUTIONS:** The listed transportation information applies only to ground transport and does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the shipper and the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. Local Government regulations and rules should prevail.

## 15. REGULATORY INFORMATION

### UNITED STATES FEDERAL REGULATIONS:

**OSHA:** OSHA Hazard Communication Standard 29 CFR 1910.1200

A component(s) of this product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### SARA Section 311/312 Hazard Category - 40 CFR 370.2

This product is considered, under applicable definitions, to meet the following categories:

(X) Fire Hazard      (X) Acute Health Hazard      (X) Chronic Health Hazard

### SARA 313 Information

This product contains the following substances subject to the reporting requirements of Section 313 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and 40 CFR 372:

<u>Chemical Name</u>	<u>CAS Number</u>	
AROMATIC NAPHTHA Component:		
1,2,4-Trimethylbenzene	95-63-6	< 4.0%

### STATE REGULATIONS:

#### California Proposition 65

Warning: The following ingredients present in this product are known to the state of California to cause cancer, birth defects, or other reproductive hazards:

<u>Chemical Name</u>	<u>CAS Number</u>
AROMATIC NAPHTHA	64742-95-6
Contains: 1,2,4-Trimethylbenzene	95-63-6
Cumene	98-82-8
Xylene	1330-20-7
ALKYD Mixture Contains: Mineral Spirits	64742-88-7
Mineral Spirits Contains: Ethylbenzene	100-41-4
Cumene	98-82-8
Toluene	108-88-3

#### Right-To-Know Component Information New Jersey, Pennsylvania, Massachusetts

<u>Chemical Name</u>	<u>CAS Number</u>
AROMATIC NAPHTHA	64742-95-6
Contains: 1,2,4-Trimethylbenzene	95-63-6
Cumene	98-82-8
Xylene	1330-20-7
ALKYD Mixture Contains: Mineral Spirits	64742-88-7
Mineral Spirits Contains: Ethylbenzene	100-41-4
Cumene	98-82-8
Toluene	108-88-3
TERTIARY BUTYL ACETATE	540-88-5
TITANIUM DIOXIDE	13463-67-7

## 16. OTHER INFORMATION

### **HMIS RATING**

Health:	2
Flammability:	2
Personal Hazard:	0
Personal Protection:	J

DISCLAIMER: The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date. Wechsler Pool Supply Co. makes no representation, warranty or guarantee as to the completeness or accuracy thereof. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Version: CRPP-1

Date Prepared: 3/29/2016